



10KHz stability Ku-Band PLL LNB

KEY FEATURES

- ◆ RF frequency 10.7 - 11.8 GHz
- ◆ L.O. 9.75 GHz
- ◆ Stability +/- 10KHz
- ◆ Gain 60 dB typ.
- ◆ "N" or "F" RF interface options
- ◆ Output P1dB +5dBm min.

AL9750010 / AL9750010N



Model	RF Frequency	IF Frequency	L. O
AL9750010	10.7 - 11.8 GHz	950 - 2050 MHz	9.75 GHz
AL1000010	10.95 - 11.7 GHz	950 - 1700 MHz	10.0 GHz
AL10750010	11.7 - 12.2 GHz	950 - 1450 MHz	10.75 GHz
AL10750010E	11.7 - 12.75 GHz	950 - 2000 MHz	10.75 GHz
AL11250010	12.2 - 12.7 GHz	950 - 1450 MHz	11.25 GHz
AL11300010	12.25 - 12.75 GHz	950 - 1450 MHz	11.3 GHz

General Spec

Conversion gain	60 dB typ. (55dB min. 65dB max.)	Gain flatness	4 dB p-p Max.
Input VSWR	2.2 : 1 Typ.	Output VSWR	2.2 : 1 Typ.
IF Connector	"F" or "N" - Type Female	IF impedance	75 or 50 ohms
RF Interface	WR - 75 Waterproof	Gain Ripple	1 dB p-p max per 36 MHz
Phase Noise	1 KHz -70 dBc/Hz	Noise figure	0.8 dB Max.
	10 KHz -80 dBc/Hz	Power Supply	+12 - +24 VDC
	100 KHz -95 dBc/Hz	Current	350 mA Max.
Image Rejection	40 dBc min.	Leakage	-45 dBm Max.
Operating Temperature	-40C - +60C	Humidity	100%
Dimensions (mm)	99.5x 42 x 42	Weight (g)	300

Mechanical Drawing

